



CANYONLANDS FIRE TABLE

Long, narrow gas fire table designed as an architectural centerline feature. Eight sizes from 44" to 120", three vessel materials: mild steel, corten steel, and marine-grade aluminum. CSA-certified for outdoor installation in the U.S. Fabricated to order in Missoula, Montana.

MONTANA FIRE PITS

AMERICAN-SOURCED · MONTANA-FABRICATED

THE VENTURE SERIES



CANYONLANDS FIRE TABLE

Hand-built linear gas fire table, 22" wide, in eight sizes from 44" to 120" long. Intentional narrow ledge. Three vessel materials.

MODELS & DIMENSIONS

SKU	OUTSIDE DIM. (W × L)	BURN AREA	BTU	BURNER MODEL	WT. STEEL / ALUM.
CL44	22 × 44	38.25 × 16.25	150k / 230k	UL150 / UT230	154 / 53
CL48	22 × 48	42.25 × 16.25	170k / 230k	UL170 / UT230	164 / 57
CL56	22 × 56	50.25 × 16.25	210k / 290k	UL210 / UT290	183 / 63
CL72	22 × 72	66.25 × 16.25	270k / 350k	UL270 / UT350	222 / 77
CL84	22 × 84	78.25 × 16.25	350k / 410k	UT350 / UT410	252 / 87
CL96	22 × 96	90.25 × 16.25	470k	UT470	281 / 97
CL108	22 × 108	102.25 × 16.25	470k	UT470	310 / 107
CL120	22 × 120	114.25 × 16.25	470k	UT470	340 / 117

All dimensions in inches. Ledge 2.875" across all sizes (intentional narrow ledge). Vessel weights in pounds. Steel weight applies to mild steel and corten.

MATERIALS & CONSTRUCTION

<p>3/16" MILD STEEL American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors.</p>	<p>10 GAUGE CORTEN STEEL Weathering steel develops a stable patina over the first 12–24 months. No coating.</p>	<p>3/16" MARINE-GRADE ALUMINUM Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant.</p>		
<p>BURNER Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.</p>	<p>IGNITION Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic</p>	<p>FINISH Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.</p>	<p>ORIGIN Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.</p>	<p>LEDGE 2.875" intentional narrow ledge. Flame-forward profile suited to long terrace runs, integrated seating walls, and linear architectural features up to 10 feet long.</p>

CERTIFICATION & PERFORMANCE

<p>COMPONENTS CERTIFIED Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.</p>	Fuel Inlet	3/4" I.D. Female
	Fuel Pressure – NG	7" Water Column
	Fuel Pressure – LP	11" Water Column
	Ignition Options	Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
	Ventilation	Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

STANDARD INCLUSIONS

- Fire table vessel – 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 3/4" key valve and flex line kit
- 4" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area

OPTIONAL EXTRAS

- Thermally Modified Wood Cover (sold separately; freight applies)
- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

ORDERING

- LEAD TIME**
8–12 weeks made-to-order. Pro accounts receive priority scheduling.
- SHIPPING**
Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.
- CONTACT**
montanafirepits.com
sales@montanafirepits.com