



# OLYMPIC RISE FIRE TABLE

---

Hand-built rectangular gas fire table with elevated profile. Seven sizes, three vessel materials, three-inch toe-kick base detail. CSA-certified for outdoor installation in the U.S. Fabricated to order in Missoula, Montana.

# MONTANA FIRE PITS

AMERICAN-SOURCED · MONTANA-FABRICATED

THE VENTURE SERIES



## OLYMPIC RISE FIRE TABLE

Hand-built rectangular gas fire table with elevated profile and 3" toe-kick base detail. Seven sizes, three vessel materials.

### MODELS & DIMENSIONS

SKU	OUTSIDE DIM. (W × L)	BURN AREA	BTU	BURNER MODEL	WT. STEEL / ALUM.
OLY48-RISE	32 × 48	32.25 × 16.25	130k / 170k	UL130 / UT170	257 / 89
OLY55-RISE	32 × 55	39.25 × 16.25	150k / 230k	UL150 / UT230	284 / 99
OLY60-RISE	32 × 60	44.25 × 16.25	190k / 290k	UL190 / UT290	303 / 105
OLY67-RISE	32 × 67	51.25 × 16.25	210k / 290k	UL210 / UT290	332 / 115
OLY76-RISE	32 × 76	60.25 × 16.25	270k / 350k	UL270 / UT350	366 / 127
OLY86-RISE	32 × 86	70.25 × 16.25	410k	UT410	411 / 143
OLY96-RISE	32 × 96	80.25 × 16.25	470k	UT470	449 / 156

All dimensions in inches. Ledge 7.875". Vessel weights in pounds. Toe-kick adds 3" of base profile beneath the standard Olympic vessel.

### MATERIALS & CONSTRUCTION

#### 3/16" MILD STEEL

American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors.

#### 10 GAUGE CORTEN STEEL

Weathering steel develops a stable patina over the first 12–24 months. No coating.

#### 3/16" MARINE-GRADE ALUMINUM

Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant.

#### BURNER

Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.

#### IGNITION

Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic

#### FINISH

Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.

#### ORIGIN

Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.

#### TOE-KICK

3" recessed base detail. Elevates the vessel and adds architectural shadow line beneath the table. Standard across all Rise sizes.

### CERTIFICATION & PERFORMANCE

#### COMPONENTS CERTIFIED

Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.

Fuel Inlet	3/4" I.D. Female
Fuel Pressure — NG	7" Water Column
Fuel Pressure — LP	11" Water Column
Ignition Options	Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
Ventilation	Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

### STANDARD INCLUSIONS

- Fire table vessel — 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 3/4" key valve and flex line kit
- 4" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area

### OPTIONAL EXTRAS

- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

### ORDERING

#### LEAD TIME

8–12 weeks made-to-order. Pro accounts receive priority scheduling.

#### SHIPPING

Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.

#### CONTACT

montanafirepits.com  
sales@montanafirepits.com