



# OCTAGONAL READY-TO-FINISH FIRE PIT KIT

Steel frame with optional GoBoard surround and full Warming Trends burner kit. Octagonal form with circular burn opening. Four sizes from 36" to 60" flat-to-flat. Surface with your own veneer. CSA-certified.

# MONTANA FIRE PITS

AMERICAN-SOURCED · MONTANA-FABRICATED  
READY TO FINISH FIRE PIT KITS / FRAME + BURNER KIT



## RTF OCTAGONAL

Steel frame with optional GoBoard surround and full Warming Trends burner kit. Octagonal form with circular burn opening. Four sizes from 36" to 60" flat-to-flat. Surface with your own veneer.

### MODELS & DIMENSIONS

SKU	OUTSIDE (FLAT TO FLAT)	OPENING (DIA)	BURNER MODEL	BTU	VESSEL WT. (LBS)
RTFO36	36"	20.25 DIA	U140	140k	36
RTFO42	42"	24.25 DIA	U180	180k	54
RTFO54	54"	30.25 DIA	U240	240k	54
RTFO60	60"	36.25 DIA	U360	360k	54

All dimensions in inches. Outside dimension measured flat-to-flat (point-to-point is larger). Burn area is circular within octagonal vessel. All vessel frames 15.5" tall (16" with GoBoard).

### KIT COMPONENTS & CONSTRUCTION

#### VESSEL FRAME + GOBOARD SURROUND

Aluminum vessel frame with GoBoard concrete-board surround substrate. Installer provides exterior finish — stone, tile, masonry, or stucco.

#### VESSEL FRAME

15.5" tall aluminum frame. Four adjustable feet. Engineered for GoBoard surround integration.

#### BURNER

Warming Trends Crossfire brass burner. Certified component (ANSI Z21.97 / CSA 2.41). Same platform as finished MFP tables.

#### IGNITION

Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic

#### INSTALLATION

Installer applies exterior veneer (stone, tile, masonry, stucco). Gas line, clearances, and permits are installer's responsibility.

#### ORIGIN

Designed, fabricated, and assembled in Missoula, Montana, USA.

### CERTIFICATION & PERFORMANCE

#### COMPONENTS CERTIFIED

Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.

Fuel Inlet	3/4" I.D. Female
Fuel Pressure — NG	3.5"-14.0" Water Column (ignition-dependent)
Fuel Pressure — LP	8.0"-14.0" Water Column (ignition-dependent)
Ignition Options	Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
Ventilation	Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

#### STANDARD INCLUSIONS

- Steel vessel frame (aluminum, 15.5" tall)
- GoBoard surround substrate
- Burner pan with 2" or 3" sidewalls (per kit specification)
- Fire Pit Vent Kit (2 silver vents for on-site installation)
- Warming Trends Crossfire brass burner
- 3/4" flex line kit
- Key valve mounting bracket and 12" extension
- 12" key, adjustable feet

#### OPTIONAL EXTRAS

- Propane regulator with 10 ft hose

#### ORDERING

##### LEAD TIME

8-12 weeks made-to-order. Pro accounts receive priority scheduling.

##### SHIPPING

Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.

##### CONTACT

montanafirepits.com  
sales@montanafirepits.com