



RECTANGULAR READY-TO-FINISH FIRE PIT KIT

Steel frame with optional GoBoard surround and full Warming Trends burner kit. Eight sizes from 48" to 96" long. Surface with your own veneer — stone, tile, masonry, or stucco. CSA-certified.

MONTANA FIRE PITS

AMERICAN-SOURCED · MONTANA-FABRICATED
READY TO FINISH FIRE PIT KITS / FRAME + BURNER KIT



RTF RECTANGULAR

Steel frame with optional GoBoard surround and full Warming Trends burner kit. Eight sizes from 48" to 96" long. Surface with your own veneer — stone, tile, masonry, or stucco.

MODELS & DIMENSIONS

| SKU | OUTSIDE DIM. (L × W) | OPENING SIZE | BURNER MODEL | BTU | VESSEL WT. (LBS) |
|---------|----------------------|---------------|--------------|------|------------------|
| RTF4830 | 48 × 30 | 28.25 × 10.25 | U110 | 110k | 36 |
| RTF5532 | 55 × 32 | 39.25 × 16.25 | U230 | 230k | 54 |
| RTF6036 | 60 × 36 | 38.25 × 14.25 | U230 | 230k | 54 |
| RTF6732 | 67 × 32 | 51.25 × 16.25 | U290 | 290k | 54 |
| RTF7242 | 72 × 42 | 48.25 × 18.25 | U290 | 290k | 54 |
| RTF7632 | 76 × 32 | 60.25 × 16.25 | U350 | 350k | 54 |
| RTF8632 | 86 × 32 | 70.25 × 16.25 | U410 | 410k | 72 |
| RTF9636 | 96 × 36 | 80.25 × 20.25 | U410 | 410k | 72 |

All dimensions in inches. All vessel frames 15.5" tall (16" with GoBoard). Four feet at each corner.

KIT COMPONENTS & CONSTRUCTION

VESSEL FRAME + GOBOARD SURROUND

Aluminum vessel frame with GoBoard concrete-board surround substrate. Installer provides exterior finish — stone, tile, masonry, or stucco.

VESSEL FRAME

15.5" tall aluminum frame. Four adjustable feet. Engineered for GoBoard surround integration.

BURNER

Warming Trends Crossfire brass burner. Certified component (ANSI Z21.97 / CSA 2.41). Same platform as finished MFP tables.

IGNITION

Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic

INSTALLATION

Installer applies exterior veneer (stone, tile, masonry, stucco). Gas line, clearances, and permits are installer's responsibility.

ORIGIN

Designed, fabricated, and assembled in Missoula, Montana, USA.

CERTIFICATION & PERFORMANCE

COMPONENTS CERTIFIED

Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.

| | |
|--------------------|--|
| Fuel Inlet | 3/4" I.D. Female |
| Fuel Pressure — NG | 3.5"-14.0" Water Column (ignition-dependent) |
| Fuel Pressure — LP | 8.0"-14.0" Water Column (ignition-dependent) |
| Ignition Options | Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet). |
| Ventilation | Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation. |

STANDARD INCLUSIONS

- Steel vessel frame (aluminum, 15.5" tall)
- GoBoard surround substrate
- Burner pan with 2" or 3" sidewalls (per kit specification)
- Fire Pit Vent Kit (2 silver vents for on-site installation)
- Warming Trends Crossfire brass burner
- 3/4" flex line kit
- Key valve mounting bracket and 12" extension
- 12" key, adjustable feet

OPTIONAL EXTRAS

- Propane regulator with 10 ft hose

ORDERING

LEAD TIME

8-12 weeks made-to-order. Pro accounts receive priority scheduling.

SHIPPING

Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.

CONTACT

montanafirepits.com
sales@montanafirepits.com