



SQUARE WITH ROUND OPENING READY-TO-FINISH KIT

Steel frame with optional GoBoard surround and full Warming Trends burner kit. Square outer frame with circular burn opening. Three sizes from 32" to 47". Surface with your own veneer. CSA-certified.

MONTANA FIRE PITS

AMERICAN-SOURCED · MONTANA-FABRICATED
READY TO FINISH FIRE PIT KITS / FRAME + BURNER KIT



RTF SQUARE W/ ROUND OPENING

Steel frame with optional GoBoard surround and full Warming Trends burner kit. Square outer frame with circular burn opening. Three sizes from 32" to 47". Surface with your own veneer.

MODELS & DIMENSIONS

SKU	OUTSIDE DIM. (W × L)	OPENING (DIA)	BURNER MODEL	BTU	VESSEL WT. (LBS)
RTFSRO32	32 × 32	24.25 DIA	U180	180k	36
RTFSRO38	38 × 38	30.25 DIA	U240	240k	54
RTFSRO47	47 × 47	36.25 DIA	U360	360k	54

All dimensions in inches. All vessel frames 15.5" tall (16" with GoBoard). Ledge 3.875" on RTFSRO32 and RTFSRO38; 5.375" on RTFSRO47.

KIT COMPONENTS & CONSTRUCTION

VESSEL FRAME + GOBOARD SURROUND

Aluminum vessel frame with GoBoard concrete-board surround substrate. Installer provides exterior finish — stone, tile, masonry, or stucco.

VESSEL FRAME

15.5" tall aluminum frame. Four adjustable feet. Engineered for GoBoard surround integration.

BURNER

Warming Trends Crossfire brass burner. Certified component (ANSI Z21.97 / CSA 2.41). Same platform as finished MFP tables.

IGNITION

Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic

INSTALLATION

Installer applies exterior veneer (stone, tile, masonry, stucco). Gas line, clearances, and permits are installer's responsibility.

ORIGIN

Designed, fabricated, and assembled in Missoula, Montana, USA.

CERTIFICATION & PERFORMANCE

COMPONENTS CERTIFIED

Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.

Fuel Inlet	3/4" I.D. Female
Fuel Pressure — NG	3.5"–14.0" Water Column (ignition-dependent)
Fuel Pressure — LP	8.0"–14.0" Water Column (ignition-dependent)
Ignition Options	Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
Ventilation	Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

STANDARD INCLUSIONS

- Steel vessel frame (aluminum, 15.5" tall)
- GoBoard surround substrate
- Burner pan with 2" or 3" sidewalls (per kit specification)
- Fire Pit Vent Kit (2 silver vents for on-site installation)
- Warming Trends Crossfire brass burner
- 3/4" flex line kit
- Key valve mounting bracket and 12" extension
- 12" key, adjustable feet

OPTIONAL EXTRAS

- Propane regulator with 10 ft hose

ORDERING

LEAD TIME

8–12 weeks made-to-order. Pro accounts receive priority scheduling.

SHIPPING

Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.

CONTACT

montanafirepits.com
sales@montanafirepits.com