



REDWOOD FIRE TABLE

Hand-built gas fire table available in rectangle and square forms. Seven sizes, three vessel materials: mild steel, corten steel, and marine-grade aluminum. CSA-certified for outdoor installation across the U.S. Fabricated to order in Missoula, Montana.

MONTANA FIRE PITS

AMERICAN-SOURCED · MONTANA-FABRICATED

THE VENTURE SERIES



REDWOOD FIRE TABLE

Hand-built gas fire table in rectangular and square configurations. Seven total sizes. Three vessel materials.

MODELS & DIMENSIONS

SKU	OUTSIDE DIM. (W × L)	BURN AREA	BTU	BURNER MODEL	WT. STEEL / ALUM.
RECTANGULAR					
RW35x48	35 × 48	28.25 × 9.25	120k / 160k	UH120 / UH160	255 / 98
RW48x82	48 × 82	custom	custom	custom	custom
RW48x108	48 × 108	custom	custom	custom	custom
RW58x82	58 × 82	custom	custom	custom	custom
SQUARE					
RW36x36	36 × 36	18.25 × 18.25	100k / 140k	U100 / U140	210 / 83
RW48x48	48 × 48	30.25 × 30.25	180k / 240k	U180 / U240	320 / 132
RW58x58	58 × 58	36.25 × 36.25	300k / 360k	U300 / U360	425 / —

All dimensions in inches. Vessel weights in pounds. Sizes marked 'custom' are made-to-order configurations; contact your rep for specifications and lead time. RW58x58 ships in mild steel only (no aluminum variant).

MATERIALS & CONSTRUCTION

3/16" MILD STEEL American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors.	10 GAUGE CORTEN STEEL Weathering steel develops a stable patina over the first 12–24 months. No coating.	3/16" MARINE-GRADE ALUMINUM Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant.		
BURNER Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.	IGNITION Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic	FINISH Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.	ORIGIN Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.	LEDGE 7.875" symmetric ledge on square sizes. Rectangular ledges vary by SKU — see matrix and spec drawings.

CERTIFICATION & PERFORMANCE

COMPONENTS CERTIFIED Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.	Fuel Inlet	3/4" I.D. Female
	Fuel Pressure — NG	7" Water Column
	Fuel Pressure — LP	11" Water Column
	Ignition Options	Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
	Ventilation	Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

STANDARD INCLUSIONS

- Fire table vessel — 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 3/4" key valve and flex line kit
- 4" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area

OPTIONAL EXTRAS

- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

ORDERING

LEAD TIME

8–12 weeks made-to-order. Pro accounts receive priority scheduling.

SHIPPING

Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.

CONTACT

montanafirepits.com
sales@montanafirepits.com