



SEQUOIA FIRE TABLE

Hand-built round gas fire table with aluminum frame, GoBoard surround, and Arbor Wood Co. thermally modified ash overlay. Five diameters. Top cap in stone, tile, or concrete. CSA-certified for outdoor installation in the U.S. Fabricated to order in Missoula, Montana.

SEQUOIA FIRE TABLE

Hand-built round gas fire table with aluminum frame, GoBoard surround, and Arbor Wood overlay. Five sizes from 36" to 60" diameter. Top cap in stone, tile, or concrete.

MODELS & DIMENSIONS

SKU	DIAMETER	BURN AREA	BTU	BURNER MODEL	WT. STEEL / ALUM. (BASE)
SEQ36	36"	20.25 DIA	140k	U140	203 / 124
SEQ42	42"	26.25 DIA	180k	U180	237 / 145
SEQ48	48"	32.25 DIA	300k	U300	267 / 165
SEQ54	54"	38.25 DIA	360k	U360	304 / 186
SEQ60	60"	44.25 DIA	360k	U360	338 / 207

All dimensions in inches. Total vessel height 16.75". Weights in pounds and pending final confirmation (composite base stored without Arbor wood).

MATERIALS & CONSTRUCTION

COMPOSITE CONSTRUCTION

Top: 3/16" mild steel, powder-coat. Base: aluminum frame, GoBoard concrete substrate, Arbor Wood Co. thermally modified ash exterior. Cutek Oil finish. Several patterns available.

BURNER

Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.

IGNITION

Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic

FINISH

Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.

ORIGIN

Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.

BASE CONSTRUCTION

Aluminum frame wrapped in GoBoard concrete board, overlaid with Arbor Wood Co. thermally modified ash in selectable patterns. Top cap (stone, tile, or concrete) is the only surface where the three vessel materials apply.

CERTIFICATION & PERFORMANCE

COMPONENTS CERTIFIED

Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.

Fuel Inlet	3/4" I.D. Female
Fuel Pressure – NG	7" Water Column
Fuel Pressure – LP	11" Water Column
Ignition Options	Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
Ventilation	Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

STANDARD INCLUSIONS

- Fire table vessel – 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 3/4" key valve and flex line kit
- 4" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area
- Arbor Wood Co. thermally modified ash base overlay (selectable patterns, Cutek Oil finish)
- Top cap selection: stone, concrete, or tile (installer-supplied or factory option)

OPTIONAL EXTRAS

- Thermally Modified Wood Cover (sold separately; freight applies)
- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

ORDERING

LEAD TIME

8-12 weeks made-to-order. Pro accounts receive priority scheduling.

SHIPPING

Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.

CONTACT

montanafirepits.com
sales@montanafirepits.com