



TETON STUDIO FIRE TABLE

Compact rectangular gas fire table with thermally modified ash accent by Arbor Wood Co. Four sizes, three vessel materials. CSA-certified for outdoor installation in the U.S. Fabricated to order in Missoula, Montana.

MONTANA FIRE PITS

AMERICAN-SOURCED · MONTANA-FABRICATED

THE VENTURE STUDIO SERIES

TETON STUDIO



Compact rectangular gas fire table with thermally modified ash side panels by Arbor Wood Co. Four sizes, three vessel materials.

MODELS & DIMENSIONS

SKU	OUTSIDE DIM. (W × L)	BURN AREA	BTU	BURNER MODEL	WT. STEEL / ALUM.
TS3222	22 × 32	12.25 × 22.25	90k	UL90	160 / 55
TS3822	22 × 38	12.25 × 28.25	110k	UL110	178 / 62
TS4222	22 × 42	12.25 × 32.25	130k	UL130	193 / 67
TS4822	22 × 48	12.25 × 38.25	150k	UL150	212 / 74

All dimensions in inches. Vessel height 16". Ledge 4.875" across all sizes. Vessel weights in pounds (without Arbor wood).

MATERIALS & CONSTRUCTION

3/16" MILD STEEL American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors.	10 GAUGE CORTEN STEEL Weathering steel develops a stable patina over the first 12–24 months. No coating.	3/16" MARINE-GRADE ALUMINUM Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant.		
BURNER Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.	IGNITION Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic	FINISH Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.	ORIGIN Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.	WOOD ACCENT Thermally modified ash by Arbor Wood Co. integrated along side panels. Cutek Oil finish. Several wood patterns available.

CERTIFICATION & PERFORMANCE

COMPONENTS CERTIFIED Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.	Fuel Inlet	1/2" I.D. Female
	Fuel Pressure – NG	7" Water Column
	Fuel Pressure – LP	11" Water Column
	Ignition Options	Match Lit (standard); Push Button Battery; Mercury Battery; Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet)
	Ventilation	Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

STANDARD INCLUSIONS

- Fire table vessel – 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 1/2" key valve and flex line kit
- 3" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area
- Arbor Wood Co. thermally modified ash side panels (Cutek Oil finish)

OPTIONAL EXTRAS

- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

ORDERING

LEAD TIME

8–12 weeks made-to-order. Pro accounts receive priority scheduling.

SHIPPING

Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.

CONTACT

montanafirepits.com
sales@montanafirepits.com