



YELLOWSTONE EDGE FIRE TABLE

Round gas fire table with a 1.5" lip that carries the burn area nearly to the rim. Available in three sizes from 36" to 48" diameter. Three vessel materials: mild steel, corten steel, and marine-grade aluminum. Built with CSA-certified burner components. Fabricated to order in Missoula, Montana.

MONTANA FIRE PITS

AMERICAN-SOURCED · MONTANA-FABRICATED

THE VENTURE SERIES



YELLOWSTONE EDGE FIRE TABLE

Hand-built round gas fire table in three sizes from 36" to 48" diameter. A 1.5" lip in place of the standard ledge.

MODELS & DIMENSIONS

| SKU | DIAMETER | BURN AREA | BTU | BURNER MODEL | WT. STEEL / ALUM. |
|-----------|----------|-----------|------|--------------|-------------------|
| YS36-EDGE | 36" | 33" Ø | 140k | U140 | 161/56 |
| YS42-EDGE | 42" | 39" Ø | 180k | U180 | 220/76 |
| YS48-EDGE | 48" | 45" Ø | 300k | U300 | 249/87 |

All dimensions in inches. Vessel height 15" across all sizes. Lip 1.5" across all sizes; burn area is the vessel opening inside the lip. Vessel weights in pounds. Steel weight applies to mild steel and corten. Burner shown as Universal round burner.

MATERIALS & CONSTRUCTION

| | | | | |
|--|--|---|--|--|
| 3/16" MILD STEEL American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors. | 10 GAUGE CORTEN STEEL Weathering steel develops a stable patina over the first 12–24 months. No coating. | 3/16" MARINE-GRADE ALUMINUM Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant. | | |
| BURNER Warming Trends Crossfire brass burner. Solid brass. Patented jet technology. | IGNITION Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic | FINISH Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating. | ORIGIN Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order. | EDGE PROFILE 1.5" lip across all sizes. The burn area extends to within 1.5" of the rim. |

CERTIFICATION & PERFORMANCE

| | | |
|--|---------------------------|--|
| COMPONENTS CERTIFIED Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components. | Fuel Inlet | 3/4" I.D. Female |
| | Fuel Pressure – NG | 7" Water Column |
| | Fuel Pressure – LP | 11" Water Column |
| | Ignition Options | Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet). |
| | Ventilation | Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation. |

STANDARD INCLUSIONS

- Fire table vessel – 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 3/4" key valve and flex line kit
- 4" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area

OPTIONAL EXTRAS

- Thermally Modified Wood Cover (sold separately; freight applies)
- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

ORDERING

- LEAD TIME**
8–12 weeks made-to-order. Pro accounts receive priority scheduling.
- SHIPPING**
Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.
- CONTACT**
montanafirepits.com
sales@montanafirepits.com