



YELLOWSTONE FIRE TABLE

Round gas fire table, available in five diameters from 36" to 60". Three vessel materials: mild steel, corten steel, and marine-grade aluminum. 15" vessel height with continuous 360° ledge. CSA-certified for outdoor installation in the U.S. Fabricated to order in Missoula, Montana.

MONTANA FIRE PITS

AMERICAN-SOURCED · MONTANA-FABRICATED

THE VENTURE SERIES



YELLOWSTONE FIRE TABLE

Hand-built round gas fire table in five sizes from 36" to 60" diameter. Three vessel materials.

MODELS & DIMENSIONS

SKU	DIAMETER	BURN AREA	BTU	BURNER MODEL	WT. STEEL / ALUM.
YS36	36"	16 DIA	100k / 140k	U100 / U140	225 / 105
YS42	42"	16 DIA	140k / 180k	U140 / U180	290 / 127
YS48	48"	16 DIA	180k / 240k / 300k	U180 / U240 / U300	350 / 159
YS54	54"	16 DIA	240k / 300k / 360k	U240 / U300 / U360	425 / 195
YS60	60"	16 DIA	300k / 360k / 420k	U300 / U360 / U420	510 / 230

All dimensions in inches. Vessel height 15". Vessel weights in pounds. Steel weight applies to mild steel and corten. Burner options progress through Universal Crossfire sizes.

MATERIALS & CONSTRUCTION

3/16" MILD STEEL

American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors.

10 GAUGE CORTEN STEEL

Weathering steel develops a stable patina over the first 12–24 months. No coating.

3/16" MARINE-GRADE ALUMINUM

Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant.

BURNER

Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.

IGNITION

Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic

FINISH

Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.

ORIGIN

Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.

BURN AREA

Circular burn opening across all Yellowstone sizes.

CERTIFICATION & PERFORMANCE

COMPONENTS CERTIFIED

Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.

Fuel Inlet	3/4" I.D. Female
Fuel Pressure – NG	7" Water Column
Fuel Pressure – LP	11" Water Column
Ignition Options	Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
Ventilation	Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

STANDARD INCLUSIONS

- Fire table vessel – 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 3/4" key valve and flex line kit
- 4" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area

OPTIONAL EXTRAS

- Thermally Modified Wood Cover (sold separately; freight applies)
- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

ORDERING

LEAD TIME

8–12 weeks made-to-order. Pro accounts receive priority scheduling.

SHIPPING

Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.

CONTACT

montanafirepits.com
sales@montanafirepits.com