



YELLOWSTONE STUDIO

Compact round gas fire table designed for intimate spaces and flexible outdoor layouts. Available in three diameters from 22" to 34". Three vessel materials: mild steel, corten steel, and marine-grade aluminum. CSA-certified. Fabricated to order in Missoula, Montana.

MONTANA FIRE PITS

AMERICAN-SOURCED · MONTANA-FABRICATED

THE VENTURE STUDIO SERIES



YELLOWSTONE STUDIO

Compact round gas fire table in three sizes from 22" to 34" diameter. Three vessel materials.

MODELS & DIMENSIONS

SKU	DIAMETER	BURN AREA	BTU	BURNER MODEL	WT. STEEL / ALUM.
YSSTUDIO22	22"	custom	60k	U60	custom
YSSTUDIO28	28"	16 DIA	60k / 100k	U60 / U100	180 / 95
YSSTUDIO34	34"	16 DIA	100k / 140k / 180k	U100 / U140 / U180	220 / 110

All dimensions in inches. Vessel height 16". Vessel weights in pounds. Sizes marked 'custom' are made-to-order configurations; contact your rep for specifications and lead time.

MATERIALS & CONSTRUCTION

3/16" MILD STEEL American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors.	10 GAUGE CORTEN STEEL Weathering steel develops a stable patina over the first 12-24 months. No coating.	3/16" MARINE-GRADE ALUMINUM Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant.
BURNER Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.	IGNITION Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic	FINISH Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.
	ORIGIN Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.	BURN AREA Circular burn opening. Compact round form for balconies, terraces, and constrained gathering spaces.

CERTIFICATION & PERFORMANCE

COMPONENTS CERTIFIED Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.	Fuel Inlet 1/2" I.D. Female
	Fuel Pressure — NG 7" Water Column
	Fuel Pressure — LP 11" Water Column
	Ignition Options Match Lit (standard); Push Button Battery; Mercury Battery; Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet)
	Ventilation Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

STANDARD INCLUSIONS

- Fire table vessel — 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 1/2" key valve and flex line kit
- 3" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area

OPTIONAL EXTRAS

- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

ORDERING

- LEAD TIME**
8-12 weeks made-to-order. Pro accounts receive priority scheduling.
- SHIPPING**
Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.
- CONTACT**
montanafirepits.com
sales@montanafirepits.com