



# ZION FIRE TABLE

---

Square gas fire table with circular burn opening. Available in three sizes. Three vessel materials: mild steel, corten steel, and marine-grade aluminum. CSA-certified. Fabricated to order in Missoula, Montana.

# MONTANA FIRE PITS

AMERICAN-SOURCED · MONTANA-FABRICATED

THE VENTURE SERIES

## ZION FIRE TABLE



Hand-built square gas fire table with round burn opening. Three sizes. Three vessel materials.

### MODELS & DIMENSIONS

SKU	OUTSIDE DIM. (W × L)	BURN AREA (DIA)	BTU	BURNER MODEL	WT. STEEL / ALUM.
ZN32	32 × 32	16"	100k / 140k / 180k	U100 / U140 / U180	300 / 167
ZN38	38 × 38	24"	180k / 240k / 300k	U180 / U240 / U300	350 / 184
ZN47	47 × 47	30"	240k / 300k	U240 / U300	425 / 212

All dimensions in inches. Vessel weights in pounds. Square outer frame with circular burn opening.

### MATERIALS & CONSTRUCTION

#### 3/16" MILD STEEL

American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors.

#### 10 GAUGE CORTEN STEEL

Weathering steel develops a stable patina over the first 12–24 months. No coating.

#### 3/16" MARINE-GRADE ALUMINUM

Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant.

#### BURNER

Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.

#### IGNITION

Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic

#### FINISH

Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.

#### ORIGIN

Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.

#### BURN OPENING

Circular burn area within square outer frame. Clean base construction. Geometric contrast between architectural anchor and organic flame.

### CERTIFICATION & PERFORMANCE

#### COMPONENTS CERTIFIED

Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.

Fuel Inlet	3/4" I.D. Female
Fuel Pressure – NG	7" Water Column
Fuel Pressure – LP	11" Water Column
Ignition Options	Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
Ventilation	Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

### STANDARD INCLUSIONS

- Fire table vessel – 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 3/4" key valve and flex line kit
- 4" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area

### OPTIONAL EXTRAS

- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

### ORDERING

#### LEAD TIME

8–12 weeks made-to-order. Pro accounts receive priority scheduling.

#### SHIPPING

Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.

#### CONTACT

montanafirepits.com  
sales@montanafirepits.com