

IGNITION LEVEL:
**PREMIUM
AUTOMATIC**

BEST FOR:
**HIGH BTU /
PREMIUM INSTALLATIONS**

STEP UP FROM:
COBALT

HIGHEST OUTPUT:
**HIGH CAPACITY
680K BTU**

PLATINUM


IGNITION SYSTEM™

Maximum Performance. Engineered for Demanding Installations.

The most powerful ignition system in the Catalyst lineup—built for high BTU fire features and long-term reliability.



MSRP **\$2,259**

 **680,000
BTU OUTPUT**

 **24V LOW
VOLTAGE**

 **HOT SURFACE
IGNITION**

 **HIGH-BTU
APPLICATIONS**


 **NG / LP
FUEL**

WHY CHOOSE PLATINUM

- ✓ Engineered for high-BTU premium fire feature installations
- ✓ Onboard LED diagnostics for instant troubleshooting
- ✓ Ideal for large-scale fire features
- ✓ Automatic ignition with re-lighting + safety shut-off
- ✓ Designed to eliminate common ignition failures in outdoor environments

PILOT DESIGN ADVANTAGES

NEW! Redesigned to work seamlessly with any burner system

 Proprietary wind cage design: prolongs life of pilot components; provides outstanding protection against rain; prevents blow outs from wind



POWERED BY CATALYST™ IGNITION TECHNOLOGY

Backed by Warming Trends' trusted technology and field-proven reliability.

VISIT US ONLINE
TO LEARN MORE






HOW IT WORKS



Flip a switch for immediate ignition



Gas valve opens → burner ignites



If flame blows out → automatic relighting



If relighting is unsuccessful → safety shut off

INDUSTRY-STANDARD WARRANTY



RESIDENTIAL WARRANTY



COMMERCIAL WARRANTY

SPECIFICATIONS

Max BTU Output:	680,000 BTU/hr
Voltage:	24 volt
Ignition Type:	Hot Surface Ignition
Pilot:	PCB Controlled
Fuel:	Natural Gas or Liquid Propane
Weather Resistant:	Yes
Certification:	CSA Certified
Warranty:	3-Year Residential / 1-Year Commercial

ORDERING INFORMATION

PRODUCT DESCRIPTION	SKU	FUEL	MSRP
Platinum Ignition System - Hot Surface Igniter + 24V Transformer + for 1/2" Manifolds. Maximum Gas Output 680K BTU/hr	103063	Natural Gas	\$2,259
	103064	Liquid Propane	
Platinum Ignition System - Hot Surface Igniter + 24V Transformer + for 3/4" Manifolds. Maximum Gas Output 680K BTU/hr	103065	Natural Gas	
	103066	Liquid Propane	

THE CATALYST IGNITION LINEUP

	MERCURY (Standing Pilot)	CARBON (Automatic)		COBALT (Automatic)	PLATINUM (Automatic)
POWER		Battery 	Direct Wire 		
VOLTAGE	Low Voltage	Low Voltage	Low Voltage	Low Voltage	Standard
MAX BTU OUTPUT	240,000 BTUs	360,000 BTUs	360,000 BTUs	490,000 BTUs	680,000 BTUs
BEST FOR	Moderate BTUs or remote installs	Single installs near water or remote installs	Single installs near water or mid-level BTUs	Premium or multi-unit installs near water or mid-to-high tier BTUs	Premium or multi-unit & high BTU installations

