



GLACIER RIDGE FIRE TABLE

Hand-built square gas fire table with 2" tapered sides and a 1" flat top overhang. Available in four sizes from 34" to 56". Three vessel materials: mild steel, corten steel, and marine-grade aluminum. CSA-certified for outdoor installation in the U.S. Fabricated to order in Missoula, Montana.

GLACIER RIDGE FIRE TABLE

Hand-built square gas fire table with 2" tapered sides and a 1" flat top overhang. Four sizes, three vessel materials.

MODELS & DIMENSIONS

SKU	OUTSIDE DIM. (W × L)	BURN AREA	BTU	BURNER MODEL	WT. STEEL / ALUM.
GLA34-RIDGE	34 × 34	18.25 × 18.25	100k	U100	198 / 69
GLA40-RIDGE	40 × 40	24.25 × 24.25	180k	U180	248 / 86
GLA46-RIDGE	46 × 46	30.25 × 30.25	240k	U240	298 / 104
GLA56-RIDGE	56 × 56	36.25 × 36.25	360k	U360	382 / 133

All dimensions in inches. Ledge 7.875" on 34–46; 9.875" on the 56". Apron height 15.75". Vessel weights in pounds. Steel weight applies to mild steel and corten.

MATERIALS & CONSTRUCTION

3/16" MILD STEEL		10 GAUGE CORTEN STEEL		3/16" MARINE-GRADE ALUMINUM	
American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors.		Weathering steel develops a stable patina over the first 12–24 months. No coating.		Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant.	
BURNER		IGNITION		PROFILE	
Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.		Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic		2" tapered sides rise to a 1" flat top overhang. Recessed apron gives the vessel a lifted, architectural stance across all four sizes.	
FINISH		ORIGIN			
Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.		Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.			

CERTIFICATION & PERFORMANCE

COMPONENTS CERTIFIED Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.	Fuel Inlet 3/4" I.D. Female
	Fuel Pressure — NG 7" Water Column
	Fuel Pressure — LP 11" Water Column
	Ignition Options Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
	Ventilation Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

STANDARD INCLUSIONS

- Fire table vessel — 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 3/4" key valve and flex line kit
- 4" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area

OPTIONAL EXTRAS

- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

ORDERING

- LEAD TIME
- 8–12 weeks made-to-order. Pro accounts receive priority scheduling.
- SHIPPING
- Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.
- CONTACT
- montanafirepits.com
sales@montanafirepits.com