



BADLANDS FIRE TABLE

Hand-built round gas fire table with sculpted apron profile. Five diameters, three vessel materials: mild steel, corten steel, and marine-grade aluminum. CSA-certified for outdoor installation in the U.S. Fabricated to order in Missoula, Montana.

MONTANA FIRE PITS

 AMERICAN-SOURCED · MONTANA-FABRICATED

THE VENTURE SERIES

MONTANA
FIRE PITS

BADLANDS FIRE TABLE

Hand-built round gas fire table in five sizes from 36" to 60" diameter. T16 B10 A6 profile. Three vessel materials.

MODELS & DIMENSIONS

SKU	DIAMETER	BURN AREA	BTU	BURNER MODEL	WT. STEEL / ALUM.
BAD36	36"	20.25 DIA	140k	U140	211 / 73
BAD42	42"	26.25 DIA	180k	U180	283 / 98
BAD48	48"	32.25 DIA	300k	U300	323 / 112
BAD54	54"	38.25 DIA	360k	U360	380 / 132
BAD60	60"	44.25 DIA	360k	U360	446 / 155

All dimensions in inches. T16 B10 A6 profile: 16" top vessel, 10" base, 6" apron. Total height with feet approximately 32". Vessel weights in pounds. Steel weight applies to mild steel and corten.

MATERIALS & CONSTRUCTION

3/16" MILD STEEL		10 GAUGE CORTEN STEEL	3/16" MARINE-GRADE ALUMINUM	
American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors.		Weathering steel develops a stable patina over the first 12–24 months. No coating.	Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant.	
BURNER	IGNITION	FINISH	ORIGIN	PROFILE
Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.	Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic	Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.	Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.	T16 B10 A6. Top vessel 16", base 10", apron 6". Total architectural height with feet approximately 32".

CERTIFICATION & PERFORMANCE

COMPONENTS CERTIFIED Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.	Fuel Inlet 3/4" I.D. Female
	Fuel Pressure — NG 7" Water Column
	Fuel Pressure — LP 11" Water Column
	Ignition Options Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
	Ventilation Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

STANDARD INCLUSIONS - Fire table vessel — 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec) - Warming Trends Crossfire brass burner (size per matrix) 3/4" key valve and flex line kit 4" chrome key and finishing plate - Aluminum burner plate, mounted 4" below finished top 4" non-marring adjustable feet for ventilation gap - Rolled lava pebbles for burn area	OPTIONAL EXTRAS - Thermally Modified Wood Cover (sold separately; freight applies) - Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies) - Log Sets - Glass Flame Guards - Propane regulator with 10 ft hose - Casters	ORDERING LEAD TIME 8–12 weeks made-to-order. Pro accounts receive priority scheduling. SHIPPING Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination. CONTACT montanafirepits.com sales@montanafirepits.com
--	--	--