



GLACIER FIRE TABLE

Hand-built square gas fire table available in four sizes. Three vessel materials: mild steel, corten steel, and marine-grade aluminum. CSA-certified for outdoor installation in the U.S. Fabricated to order in Missoula, Montana.

MONTANA FIRE PITS

 AMERICAN-SOURCED · MONTANA-FABRICATED

THE VENTURE SERIES

MONTANA
FIRE PITS

GLACIER FIRE TABLE

Hand-built square gas fire table in four sizes from 34" to 56". Three vessel materials.

MODELS & DIMENSIONS

SKU	OUTSIDE DIM. (W × L)	BURN AREA	BTU	BURNER MODEL	WT. STEEL / ALUM.
GLA34	34 × 34	18.25 × 18.25	100k	U100	208 / 72
GLA40	40 × 40	24.25 × 24.25	180k	U180	261 / 91
GLA46	46 × 46	30.25 × 30.25	240k	U240	314 / 109
GLA56	56 × 56	36.25 × 36.25	360k	U360	402 / 140

All dimensions in inches. Ledge 7.875". Vessel weights in pounds. Steel weight applies to mild steel and corten.

MATERIALS & CONSTRUCTION

3/16" MILD STEEL American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors.		10 GAUGE CORTEN STEEL Weathering steel develops a stable patina over the first 12–24 months. No coating.		3/16" MARINE-GRADE ALUMINUM Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant.
BURNER Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.	IGNITION Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic	FINISH Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.	ORIGIN Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.	LEDGE 7.875" usable ledge. Symmetric proportions across all four Glacier sizes.

CERTIFICATION & PERFORMANCE

COMPONENTS CERTIFIED Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.		Fuel Inlet	3/4" I.D. Female
		Fuel Pressure — NG	7" Water Column
		Fuel Pressure — LP	11" Water Column
		Ignition Options	Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
		Ventilation	Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

STANDARD INCLUSIONS

- Fire table vessel — 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 3/4" key valve and flex line kit
- 4" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area

OPTIONAL EXTRAS

- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

ORDERING

LEAD TIME
8–12 weeks made-to-order. Pro accounts receive priority scheduling.

SHIPPING
Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.

CONTACT
montanafirepits.com
sales@montanafirepits.com