



YELLOWSTONE FIRE TABLE

Round gas fire table, available in five diameters from 36" to 60". Three vessel materials: mild steel, corten steel, and marine-grade aluminum. 15" vessel height with continuous 360° ledge. CSA-certified for outdoor installation in the U.S. Fabricated to order in Missoula, Montana.

MONTANA FIRE PITS

 AMERICAN-SOURCED · MONTANA-FABRICATED

THE VENTURE SERIES

MONTANA
FIRE PITS

YELLOWSTONE FIRE TABLE

Hand-built round gas fire table in five sizes from 36" to 60" diameter. Three vessel materials.

MODELS & DIMENSIONS

SKU	DIAMETER	BURN AREA	BTU	BURNER MODEL	WT. STEEL / ALUM.
YS36	36"	20.25 DIA	140k	U140	187 / 65
YS42	42"	26.25 DIA	180k	U180	252 / 87
YS48	48"	32.25 DIA	300k	U300	287 / 100
YS54	54"	38.25 DIA	360k	U360	338 / 117
YS60	60"	44.25 DIA	360k	U360	396 / 138

All dimensions in inches. Vessel height 15". Vessel weights in pounds. Steel weight applies to mild steel and corten. One Universal Crossfire burner per size.

MATERIALS & CONSTRUCTION

3/16" MILD STEEL American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors.		10 GAUGE CORTEN STEEL Weathering steel develops a stable patina over the first 12–24 months. No coating.		3/16" MARINE-GRADE ALUMINUM Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant.	
BURNER Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.	IGNITION Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic	FINISH Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.	ORIGIN Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.	BURN AREA Circular burn opening across all Yellowstone sizes.	

CERTIFICATION & PERFORMANCE

COMPONENTS CERTIFIED Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.		Fuel Inlet	3/4" I.D. Female
		Fuel Pressure — NG	7" Water Column
		Fuel Pressure — LP	11" Water Column
		Ignition Options	Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
		Ventilation	Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

STANDARD INCLUSIONS

- Fire table vessel — 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 3/4" key valve and flex line kit
- 4" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area

OPTIONAL EXTRAS

- Thermally Modified Wood Cover (sold separately; freight applies)
- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

ORDERING

- LEAD TIME**
8–12 weeks made-to-order. Pro accounts receive priority scheduling.
- SHIPPING**
Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.
- CONTACT**
montanafirepits.com
sales@montanafirepits.com