



ZION FIRE TABLE

Square gas fire table with circular burn opening. Available in three sizes. Three vessel materials: mild steel, corten steel, and marine-grade aluminum. CSA-certified. Fabricated to order in Missoula, Montana.

ZION FIRE TABLE

Hand-built square gas fire table with round burn opening. Three sizes. Three vessel materials.

MODELS & DIMENSIONS

SKU	OUTSIDE DIM. (W × L)	BURN AREA (DIA)	BTU	BURNER MODEL	WT. STEEL / ALUM.
ZN32	32 × 32	24.25"	180k	U180	194 / 67
ZN38	38 × 38	30.25"	300k	U300	243 / 84
ZN47	47 × 47	32.25"	300k	U300	324 / 113

All dimensions in inches. Vessel weights in pounds. Square outer frame with circular burn opening.

MATERIALS & CONSTRUCTION

3/16" MILD STEEL American-sourced. Hand-welded in Missoula. Powder-coat finish in standard MFP colors.		10 GAUGE CORTEN STEEL Weathering steel develops a stable patina over the first 12–24 months. No coating.		3/16" MARINE-GRADE ALUMINUM Marine-grade aluminum. Lighter than steel. Powder-coat finish. Naturally corrosion-resistant.	
BURNER Warming Trends Crossfire brass burner. Solid brass. Patented jet technology.	IGNITION Match Lit · Push Button Battery · Mercury Battery · Carbon 3V Low Voltage · Platinum 24V Electronic	FINISH Powder-coat on mild steel and aluminum in standard MFP colors. Corten weathers without coating.	ORIGIN Designed, fabricated, and assembled in Missoula, Montana, USA. Made-to-order.	BURN OPENING Circular burn area within square outer frame. Clean base construction. Geometric contrast between architectural anchor and organic flame.	

CERTIFICATION & PERFORMANCE

COMPONENTS CERTIFIED Warming Trends Crossfire brass burners and gas ignition systems are certified to ANSI Z21.97 / CSA 2.41 for outdoor decorative gas appliances. The complete fire feature is fabricated in Missoula from these certified components.		Fuel Inlet	3/4" I.D. Female
		Fuel Pressure — NG	7" Water Column
		Fuel Pressure — LP	11" Water Column
		Ignition Options	Match Lit (standard); Push Button Battery; Mercury Battery (burners under 250K BTU); Carbon 3V Low Voltage (battery or direct-wire, up to 360K BTU); Platinum 24V Electronic (any burner; requires 110V GFI outlet).
		Ventilation	Min. 18 sq. in. of venting on each of two opposing sides of any enclosed surround. Total min. 36 sq. in. Required for LP and NG operation.

STANDARD INCLUSIONS

- Fire table vessel — 3/16" mild steel, 10 gauge corten, or 3/16" aluminum (per order spec)
- Warming Trends Crossfire brass burner (size per matrix)
- 3/4" key valve and flex line kit
- 4" chrome key and finishing plate
- Aluminum burner plate, mounted 4" below finished top
- 4" non-marring adjustable feet for ventilation gap
- Rolled lava pebbles for burn area

OPTIONAL EXTRAS

- Full Size Aluminum Cover (matches outside dimensions; sold separately; freight applies)
- Log Sets
- Glass Flame Guards
- Propane regulator with 10 ft hose
- Casters

ORDERING

LEAD TIME
8–12 weeks made-to-order. Pro accounts receive priority scheduling.

SHIPPING
Freight via crate. Outside dimensions and weights per matrix. Trade Pro accounts: contact your rep for shipping coordination.

CONTACT
montanafirepits.com
sales@montanafirepits.com